



Oslo

OS127-PSC (Pan: OS127BTW / Seat: VI1273ST)

Wall Faced Toilet Suite



All dimensions in mm

Suite includes

- Rimless Pan
- Soft close, quick release seat
- Geberit Sigma8 concealed dual flush cistern*
- Fittings & fixtures


*Flush plate sold separately

Specifications /

WELS Rating	4 star, 3.5 L avg flush volume (4.5 L / 3 L)
WELS registration number	L06556
Pan	Rimless / Easy-clean design
Traps	Universal (S or P-trap)
Set outs	S-trap set out 50 mm - 75 mm as standard. P-trap set out 185 mm floor to centre of outlet. Optional S-trap set out 140 mm - 150 mm (SPB0202).
Cistern	Geberit Sigma8 Concealed Cistern (Dual flush valve 4.5 L / 3 L)
Fixing	The toilet is fixed with a Geberit concealed water tank in wall
Seat	Soft close and quick release toilet seat is provided as standard. Compression moulded toilet seat, fitted with buffers and metal hinges.
Flush plate	Not included. Compatible with all Geberit Sigma flush plates.
Installation	The installation of the toilet suite shall be in accordance with the normal minimum drain line grade requirements in AS/NZS 3500.2.
Material / Finish	Vitreous china / Gloss white
Weight	Pan is 32.9 kg
Parts list	UF toilet seat, Geberit double flushing valve, standard pipe
Warranty	20 years vitreous china cistern and pan replacement of product; 5 years replacement seat; 2 years valves and fittings; 1 year seals and labour (refer to oliveri.com.au)
Maintenance and care instructions	All surfaces should be cleaned with mild liquid detergent or soap and water. Do not use cream cleaners or citrus based cleaning products, as they are abrasive. Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

OS127-PSC (Pan: OS127BTW / Seat: VI1273ST)

Wall Faced Toilet Suite



OPTIONAL SET OUT DRAWING

